



DATA SHEET

8303 Polypro UV 180 Matte

Polypro UV 180 Matte is outdoor PP banner and printable by Solvent, Eco-Sol, UV and Screen. With 180mic matte finish PP, media shows excellent tear and scratch resistance. Also, ideal for high quality photo graphics as well as banner application.

USEFUL INFORMATION

Parameter	Test Method	Value
Support Material		180um PP
Weight		130 gsm
Thread Count		N/A
Denier		N/A
Surface Material		Poly primer coating
White Point (Color)	CIE Spectrophotometer	L*a*b* ... 97, +0.2, +1.0
Finish		Matte(4.5@60)
Opacity		90%
Shelf time		24 Months
Application temperature		-20°C- 65°C (-4F – 150F)

APPLICATION COMPATIBILITY

Parameter	Range	Other Factors
Typical Applications	Ideal for high quality photo graphic as well as banner application	
Outdoor Durability	12 months or more, but largely dependent on environmental conditions, methods of	
Print Technology	Sol, Eco-Sol, UV	
Standard Widths	36" x 164 ft; other widths up to 60" available special order	

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents and average and is not intended for use as a specification.

New Concept Supply LLC / P.O. Box 249 / Prosper, TX 75078C

Last Revision: 20181008