



DATA SHEET

8318 Polyester Rollup Latex GB 200

Polyester Rollup Latex GB 200 is designed by 100% opaque Grey Back PET Film with poly resin coating in matte finish. Compatible for both dye and pigment ink with saturated and vivid output. With "opaque" and "layflat" quality, ideal for different portable display stand banner, POP/POS, poster, etc.

USEFUL INFORMATION

Parameter	Test Method	Value
Support Material	DIN 60001	180um Gray Back Film
Caliper	DIN 53370	8mil
Denier	DIN EN ISO 2060	-
Coating Type		20um Poly Resin Coating
Adhesive		-
Adhesive Thickness		-
Surface Material		PET
Finish	DIN 53370	Matte
Liner Type		-
Whitenss	DIN 53354	93 +/- 1
Opacity	DIN 53363	100%
Flame Resistance	NFPA 701	-
Lo Temp (No Crack at ...)	ISO 13934-1:1999	5°C (41F)
Shelf Time		12 Months

APPLICATION COMPATIBILITY

Parameter	Range	Other Factors
Typical Applications	Banners, Flags, POP Displays, Signs	
Outdoor Durability	Up to 6 Months Indoor, but largely dependent on environmental conditions, methods of installation, printing, and post-print finishing.	
Print Technology	Eco/Sol, UV, Latex, Screen	
Standard Widths	30", 36", 42", 54", 60" x 164 ft - custom widths x length available by special order	

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents and average and is not intended for use as a specification.

New Concept Supply LLC / 2900 Meacham Blvd / Fort Worth, TX 76137

Last Revision: 20190819