



## DATA SHEET

### 8671 TexTac Opak Wall Fabric

TexTac Opak Wall Fabric is self - adhesive coated textiles, with 100% woven polyester fabric, PVC free. Premium coating for multiple printing including Eco-Sol, UV, Latex. Ideal for wall decor materials with removable adhesive and outdoor applications.

### USEFUL INFORMATION

Parameter	Test Method	Value
Support Material	DIN 60001	100% polyester woven
Denier	DIN EN ISO 2060	150 x 150
Coating		Poly resin
Finish		Matte
Weight	DIN 53352	120 gsm
Adhesive		White removable
Tear	DIN 53363	350 x 350 N
Flame Resistance	NFPA 701	customized for NFPA701, B2 on request
Application temperature		41-266 F (5-130°C)
Shelf time		24 Months

### APPLICATION COMPATIBILITY

Parameter	Range	Other Factors
Typical Applications	Adhesive Signage, Exhibits Events, Art Graphic, Floor & Wall Décor	
Outdoor Durability	24 months more, but largely dependent on environmental conditions and methods of installation, printing, and post-print finishing	
Print Technology	Sol, Eco-Sol, UV, Latex, Screen	
Standard Widths	54" x 164 ft - custom widths x length available by special order	

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents an average and is not intended for use as a specification.

New Concept Supply LLC / P.O. Box 249 / Prosper, TX 75078C

Last Revision: 20181008