



## DATA SHEET

### 8674 MagTac White PET SOLTX 8 mil

MagTac White PET SOLTX 8 mil is designed in 75 mic white PET film one side with 30 mic resin coating and the other side with 100-110mic ferrous coating. MagTac is regular pet film for magnetic receptive, also compatible for eco-solvent, UV curable and Latex printing.

### USEFUL INFORMATION

Parameter	Test Method	Value
Support Material	DIN 60001	PET
L. A. B. Value		92.5, -0.3, -5.9
Coating		Poly resin
Finish		Matte
Weight	DIN 53352	310 g
Mag. Force (standard sheet)		10 g/cm <sup>2</sup>
Thickness		200 um
Application temperature		-4 - 158 F (-20 -70°C)
Shelf time		12 Months

### APPLICATION COMPATIBILITY

Parameter	Range	Other Factors
Typical Applications	Exhibition, POP, Retail, Signage, Home/Office Décor	
Outdoor Durability	12 months more, but lsgely dependent on environmental conditions and methods of installation, printing, and post-print finishing	
Print Technology	Sol, Eco-Sol, UV, Latex, Screen	
Standard Widths	54" x 164 ft - custom widths x length available by special order	

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents and average and is not intended for use as a specification.

New Concept Supply LLC / 2900 Meacham Blvd / Fort Worth, TX 76137